

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
11 November 2004 (11.11.2004)

PCT

(10) International Publication Number  
**WO 2004/096043 A1**

(51) International Patent Classification<sup>7</sup>: A61B 5/08,  
G01N 21/03, 33/497, B29C 45/18

(21) International Application Number:  
PCT/SE2004/000617

(22) International Filing Date: 22 April 2004 (22.04.2004)

(25) Filing Language: Swedish

(26) Publication Language: English

(30) Priority Data:  
0301218-4 25 April 2003 (25.04.2003) SE

(71) Applicant (for all designated States except US):  
PHASE-IN AB [SE/SE]; Box 151, S-111 73 Stock-  
holm (SE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): ECKERBOM, An-  
ders [SE/SE]; Pl 669, S-185 41 Vaxholm (SE). ZYZAN-  
SKI, Robert [SE/SE]; Eriksbergsgatan 13, S-114 30 Stock-  
holm (SE).

(74) Agents: KARLSTRÖM, Lennart et al.; Noréns Patent-  
byrå AB, Box 10198, S-100 55 Stockholm (SE).


(81) Designated States (unless otherwise indicated, for every  
kind of national protection available): AE, AG, AL, AM,  
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,  
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,  
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,  
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,  
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,  
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,  
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,  
ZW.

(84) Designated States (unless otherwise indicated, for every  
kind of regional protection available): ARIPO (BW, GH,  
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Euro-  
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,  
GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK,  
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,  
ML, MR, NE, SN, TD, TG).

Published:  
— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: AN AIR GAS ANALYZER WINDOW AND A METHOD FOR PRODUCING SUCH A WINDOW



(57) Abstract: The invention relates to a window for use in an  
adapter (3) for an IR gas analyser for the analysis of breathing  
gases, where the gases flow through a through-penetrating  
passageway (9) in the adapter (3), which includes windows (8)  
disposed on opposite sides of the passageway (9) so as to enable  
an IR beam to be sent through the windows (8) and through the  
passageway (9) containing said breathing gases. Each window  
(8) is a one-piece structure comprised of plastic material and has  
a round basic shape that includes a surrounding edge (8'') and a  
central part (8') which is sunken in relation to the surrounding edge  
(8'') and which forms the window through which the IR beams or  
rays shall be able to pass. The invention also relates to a method  
of producing such a window, wherein the window (8) is formed  
by injection moulding a thermoplastic material in a mould where  
injection of the plastic material into the mould is effected centrally  
in the centre of the ultimate or forthcoming window.

WO 2004/096043 A1

## AN IR GAS ANALYSER WINDOW AND A METHOD OF PRODUCING SUCH A WINDOW

The present invention relates to an IR gas analyser window  
5 for particular use with an adapter of an IR gas analyser for  
the analysis of respiratory gases. The invention also relates  
to a particular method of producing such a window.

Main flow measuring gas analysers calculate the composition  
10 of the respiratory gases of a patient, by sending infrared  
light through the respiratory tract of the patient and  
therewith measuring the absorption of said light at chosen  
wavelengths. For the sake of accuracy, main flow measuring  
gas analysers are placed as close as possible to the pa-  
15 tient's mouth.

In order to enhance the efficiency of such respiratory gas  
measuring processes, there has recently been adopted the use  
of adapters that are inserted in the respiratory circuit and  
20 through which the respiratory gases are allowed to pass,  
while, at the same time, coupling a measuring instrument to  
the adapter for registering the gases that pass therethrough.

A gas analyser adapter is known from, for instance, the In-  
25 ternational Patent Application PCT/SE02/01528 (Publication  
No. WO 03/017837). This adapter is intended for co-action  
with a measuring head known from the International Patent  
Application PCT/SE02/01946 (Publication No. WO 03/060490).  
The adapter includes a window which constitutes a delimita-  
30 tion of a gas passageway through which the gas to be analysed  
flows, and the analysis is effected by sending a beam of  
infrared light through a window on one side of the gas pas-  
sageway and further through the gas present in said passage-  
way, and through a corresponding window on the other side of

the gas passageway, where said beam is received by an IR detector.

Similar adapters are known, for instance, from U.S. Patent Specifications 5,616,923; 6,095,986; 6,216,692; and 6,258,040.

A particular problem that has been observed in respect of the aforesaid types of adapter resides in the moisture deposits that can occur on the inside of the adapter walls. These deposits are due to the fact that the respiratory gases contain a great deal of moisture and because the moisture contained condenses inside the adapter due to the difference in temperature between the respiratory gas present in the adapter and the considerably colder ambient air on the outside of the adapter, wherein said moisture is deposited in water droplet form, inter alia on the windows in the adapter.

The windows through which the IR rays shall pass have been found to be a problematic source in those adapters of the aforesaid kind known hitherto. The requirements that should preferably be placed generally on the windows included in adapters of the aforesaid kind are:

- That the windows shall allow IR rays to pass through in the desired wavelength range.
- That the windows shall positively eliminate any condensation problems emanating from the gases in the respiratory circuit.
- That the windows shall not be deformed by mechanical action or as a result of pressure changes in the respiratory circuit.
- That surface collection of liquid shall be counteracted.
- That the windows can be mounted in the adapter in a gas-tight manner.

- That the windows have a low production cost.
- That it shall be possible to mount the windows in the adapter in a simple and inexpensive manner.

5 The following problems have been observed among the various solutions proposed with regard to window designs:

- Traditional gas windows are expensive and often need to be heated in order to avoid moisture deposits. Heating has the additional disadvantage of utilising power and also  
10 lengthens the time before which the sensor can begin to be used. Heating also results in different material compositions that make recovery of the adapters used difficult to achieve.
- Foils that are sufficiently strong mechanically normally  
15 have a poor transmission capacity in high wavelength regions. It has also been found difficult to flatten foil, therewith requiring some form of stretching or tensioning means, which, in turn, renders the elements twist responsive. Normally, additional fastener elements are required  
20 to mount the foils flush with the inner wall, so as to prevent the formation of pockets that are able to collect liquid around the window. It is often also necessary to glue these additional fastener elements, in order to obtain a secure and tight fastening.
- The different component parts and the mounting steps in-  
25 volved make manufacture of the product expensive. As mentioned above, the use of different materials also results in recovery problems.

30 Accordingly, the object of the present invention is to provide a novel window for gas analysers of the aforesaid kind with which the above described problems and drawbacks associated with windows of this kind known hitherto are avoided.

This object of the invention is achieved with a window of the aforesaid kind which is formed in one piece from a plastic material and which has a round basic shape with a surrounding or peripheral edge and a central part which is sunken in relation to said edge and which forms the window through which the IR rays shall be able to pass.

According to one preferred embodiment, the central part of said window is arched somewhat away from the surrounding edge.

According to another preferred embodiment of the invention, the window is comprised of a plastic material of the same kind as that used for the adapter in which the window shall be mounted.

According to another preferred embodiment of the invention, the window is designed to enable it to be fastened in the adapter by means of gluing, ultrasound welding or heat welding.

The aforesaid window design solution provides a window of particular construction suitable for injection moulding. However, it has not earlier been possible to injection mould such a window of sufficient thinness, about 80-90  $\mu\text{m}$ , and uniform material thickness in that part of the window through which the major part of the IR rays shall pass. Traditional injection moulding methods easily result in deficient leveling of the thin section, which has limited the minimum thickness to about 250-300  $\mu\text{m}$ . Other production methods, such as die embossing enable the thickness to be brought down to about 150-200  $\mu\text{m}$ . However, in order to achieve satisfactory transmission properties, it is necessary for the thin section



of the window thickness to be at most 90  $\mu\text{m}$ . Accordingly, a further object of the present invention is to provide a method of producing such a window.

5 This further object of the invention is achieved by a window manufacturing method in which the window is formed by injection moulding a thermoplastic material in a mould where said plastic material is injected into the mould centrally in the middle of the ultimate or forthcoming window.

10

According to one preferred embodiment of said inventive method, a surface tension modifying substance is admixed with the plastic material prior to the injection moulding process.

15 According to another preferred embodiment of the inventive method, injection moulding is carried out in a preheated mould tool.

The invention will now be described in more detail with reference to a pair of non-limiting embodiments illustrated in the accompanying drawings, of which Fig. 1 illustrates the IR-absorption spectrum of different gases measured by a gas analyser, more specifically in Fig. 1a the IR-absorption spectrum for  $\text{CO}_2$  and  $\text{N}_2\text{O}$ , in Fig. 1b the IR-absorption spectrum for anaesthetic gases, and in Fig. 1c the IR-absorption spectrum for separate anaesthetic gases in the wavelength region of 8-9.5  $\mu\text{m}$ ; Fig. 2 is a principle illustration of a patient breathing via a gas analyser; Fig. 3a is a perspective view of a gas analyser adapter; Fig. 3b is a longitudinal perspective view of an adapter according to Fig. 3a; Fig. 3c is a perspective longitudinal sectioned view of an adapter according to Fig. 3a with water droplets (mist) inside the adapter; Fig. 4a illustrates schematically the path of the rays in respect of a water droplet of larger contact angle

Fig. 4b illustrates a corresponding ray or beam path in the case of a water droplet of slightly smaller contact angle; Fig. 5a is a longitudinally sectioned view of a gas analyser adapter for a window constructed in accordance with the invention; Fig. 5b illustrates part of the longitudinal section shown in Fig. 5a in larger scale, namely the parts of a centre section of the adapter that includes windows according to the present invention; Fig. 6 is a cross-sectional view of an inventive window, shown in a much larger scale; Fig. 7 illustrates part of an injection moulding nozzle and a window, both in cross-section, in the manufacture of the window; and Fig. 8 is a schematic illustration of the course taken in moulding of the window in accordance with the inventive method.

As before mentioned, Fig. 1 illustrates IR light absorption spectra in respect of the analysis of respiratory gases with the aid of an IR gas analyser. As will be seen from Fig. 1a, the absorption spectra of CO<sub>2</sub> and N<sub>2</sub>O lie in the region of 4-4.5  $\mu\text{m}$ , which is the region in which windows used hitherto exhibit good transmittance. In distinction, the windows used hitherto have poor transmittance in the region of 8-10  $\mu\text{m}$ , which, as evident from Fig. 1b, is the region where the best absorption peaks for anaesthesia gases are found. Fig. 1c illustrates more specifically the absorption spectrum of the most common anaesthesia gases, from which it will be clearly seen that these absorption spectra are mainly found in the region of 8-9.5  $\mu\text{m}$ . Accordingly, an object of the present invention has been the provision of a window which will provide good transmittance also at these wavelengths of the infrared light.

Fig. 2 illustrates the general principle of how respiratory gases to/from a patient are analysed. The patient 1 breathes via a hose 2 which is connected to an adapter 3. Connected to the adapter 3 are respirator hoses 4 that are responsible for the supply of air/breathing gas to/from the patient 1. The adapter 3 is fitted with a measuring head 5, for instance of the kind described in the aforesaid PCT/SE02/01946, said measuring head 5 containing electronics for the emission of infrared light and the analysis of the infrared light received, and is connected to a signal cable 6 for conducting the results to a registration/indicating device, for instance a personal computer. The adapter 3 includes the windows that are the subject of the present invention and through which the infrared light passes in the measuring head 5.

15

As will be evident from Fig. 3a, the adapter 3 has two ends 3' and 3" that carry respective connections for the patient hose 2 and the respirator hose 4. The adapter also includes a centre part 7 to which the measuring head 5 can be fitted and in which the inventive windows 8 are provided. Extending through the adapter is a through-penetrating passageway 9 that leads the breathing gases from the patient hose 2 to the respirator hose 4, and vice versa. Two windows 8 are disposed opposite one another in the centre part 7, so that IR rays sent through one window 8 by the measuring head 5 will pass through the passageway 9 containing the breathing gases and out through the other window 8 on the other side of the centre part 7. Fig. 3b illustrates the ideal case in which no water droplets precipitate in the passageway 9, whereas Fig. 3c illustrates the case in which water droplets precipitate in the passageway 9 and also settle on the inner surface of the window 8.



The problems caused by water droplets that settle on the inner surface of the window 8 will be described with the aid of Fig. 4. If no measures to prevent/reduce the build-up of water droplets on the inside of window 8 a large water droplet 10 forms on the inside of said window, as illustrated in Fig. 4a, and a relatively large contact angle will be obtained between the window 8 and the water droplet 10, resulting in a relatively large angle of incidence of an incident ray on the surface of said droplet, with the subsequent reflection of the entire ray. This thus prevents the infrared light ray from passing through the through-penetrating passageway in the adapter, therewith making it impossible to effect any measurement. On the other hand, if measures have been taken to prevent/reduce the formation of water droplets on the inside of the window, as in the Fig. 4b illustration, the contact angle between the window 8 and the water droplet 10 will be relatively small, wherewith the angle of incidence of an incident ray against the surface of the water droplet will also be relatively small and the ray is able to pass the surface of said droplet 10 with only small refraction and pass through the through-penetrating passageway containing the gas to be analysed, and consequently exit through the window on the opposite side of the passageway and allow the gas to be measured and analysed.

25

Purely technically, the formation of droplets on the inside of a plastic window is explained by the difference in surface tension between the plastic surface and the water. Traditional polyolefins are highly hydrophobic, wherein the droplets that form obtain a large contact angle. The difference in surface tension between the plastic surface and the water can be eliminated by adding a surface tension modifying agent, wherewith the contact angle is reduced towards zero and the water is dispersed as a uniform film over the plastic

30

surface. In order for a surface tension modifying substance to function, it must be present on the surface of the polymer and also be at least slightly soluble in water. Those surface tension modifying agents used have this property and function so that the surface tension modifying substance present in the polymer migrates towards the plastic surface where said substance decreases on the actual surface by dissolving in the water present on said surface, therewith achieving automatic replenishment of the surface tension modifying substance so that a generally constant proportion of said substance is on hand on the plastic surface. Typical concentrations of such surface tension modifying substances are 1-3%.

Fig. 5a is a longitudinally sectioned view of an adapter 3 which includes an inventive window in two mutually opposing walls of the centre part 7 of the adapter. Fig. 5b illustrates a portion of the adapter centre part 7, more particularly the portion in which the windows are disposed in the walls of said centre part 7, whereas Fig. 6 illustrates a window 8 in larger scale.

In accordance with the invention, the window 8 is formed as a one-piece structure from plastic material and has a round basic shape, so as to simplify manufacture and mounting of the window. The window has a surrounding outer edge 8" and a central part 8' which is sunken in relation to the edge 8" and which constitutes the translucent part of the window. The central part 8' will preferably have a size of about 80-90  $\mu\text{m}$ , so as to provide good transmission throughout the entire desired wavelength range of 4-10  $\mu\text{m}$ . The surrounding edge 8" is suitably several times thicker than the central part 8', e.g. with a thickness of about 1 mm, partly to provide a stable window and partly to facilitate handling of the window 8 when fitting the same to an adapter 3. The central part 8'

of the window is also suitably caused to arch slightly away from the surrounding outer edge 8", so as to allow moisture collecting on the window to run off more easily. The window will conveniently have a gradual transition from the thicker surrounding edge 8" towards the thinner central part 8'. This results in a stronger window, which is also easier to injection mould.

As will be seen from Fig. 5b, the window 8 is mounted on the centre part 7 of the adapter wall, wherein the centre part 7 is given in manufacture an opening that includes a ledge which facilitates fitting of the window 8. The window 8 and the wall opening are conveniently dimensioned so that the centre part 8' of the window will lie generally flush with the inner wall surface 7' of the centre part, such as to avoid the formation of liquid-collecting pockets between the window 8 and the inner wall surface 7' or to avoid the occurrence of turbulent flows in the through-penetrating passageway 9. When the central part 8' of the window is also arched so as to bulge slightly into the passageway, i.e. slightly beyond the surface of the inner wall surface 7', the runoff of any moisture on the window is also facilitated.

The window 8 is suitably made of a polyolefin, which can be readily injection moulded, for instance a polyethylene and then preferably an HD polyethylene. The adapter 3 itself may consist of an injection moulded polyolefin therewith constructing the adapter as a whole, including the window, of one and the same material, which facilitates recovery of the material and constitutes good material selection from an environmental aspect.

The runoff of water from the window 8 can be facilitated by conveniently treating the window with a surface tension modi-

5 flying substance that will prevent the build-up of large water droplets, such as the droplets shown in Fig. 4a, on the inside of the window. A surface tension modifying substance may conveniently be included in the material from which the window is made, so as to avoid the need of further treating the window subsequent to its manufacture.

10 A window 8 of the aforescribed design can be readily fastened in the adapter, for instance by gluing or preferably by ultrasound or heat welding.

15 As before mentioned, an inventive window is suitably produced by injection moulding. Traditional injection moulding of such a product, using an ingate or a sprue at one end of the mould, can easily result in deficient spread or levelling of that part of the window that shall form the central part 8' thereof, since the spacing between the two mould halves would be very small when the product shall have a thickness solely in the order of 80-90  $\mu\text{m}$ . This would result in a large number of scrapped windows that are perforated or uneven in the central part of the window.

25 Accordingly, the invention also relates to a particular method of producing a window according to the invention. According to the method, the window is injection moulded from a thermoplastic substance in a mould where said substance is injected centrally into the centre of the mould, i.e. in the centre of the ultimate or forthcoming window. This is illustrated schematically in Fig. 7, which shows a window 8 according to the invention and a part of the injection moulding nozzle 11 used to inject the thermoplastic material into the mould. The mould itself has been excluded from the figure, since the mould has no great importance with regard to the invention. Fig. 8 illustrates schematically how the injected

30

thermoplastic material flows centrally in towards the centre of the bottom of the ultimate window 8, as indicated by the arrow 12. As indicated by the arrows 13, the plastic material then flows radially outwards to form the central part 8' of the window 8, and then outwards in the direction of the arrows 14 towards the surrounding edge 8". The injection mould also includes air vents 15, which extend from that part of the mould forming the surrounding edge 8" and through which air can be evacuated from the mould cavity.

10

In order to prevent the injected thermoplastic material from solidifying in that part of the mould in which the central window part 8' shall be formed, the mould is suitably heated so that the plastic material will flow out more easily and also fill that part of the mould that shall form the surrounding edge. Preheating of the mould is suitably controlled so that, during the injection process, the temperature will be at its highest in the central part of the mould cavity and then decrease gradually towards the outer part of the mould cavity.

20

The volume of air enclosed in the mould cavity can be evacuated through the radially extending air vents 15, as indicated by the arrows 16.

25

In the case of injection moulding of precision elements, such as the inventive windows, it is essential that the temperature of the mould cavity and the ingate or sprue can be controlled very accurately during the injection process. A temperature which is too low will result in incomplete filling of the thin central section, whereas a temperature that is too high can result in burning of the plastic material. Practical tests have shown that a mould cavity temperature of about 80°C and a sprue temperature of about 120°C are suitable

30



temperature magnitudes. In these tests, there was produced a window that had a diameter of 10 mm and a thickness of 80  $\mu$ m in its centre section, while using a sprue of 0.25 mm in diameter. The three radially extending air vents had a width  
5 of 0.6 mm, a thickness of 15  $\mu$ m and a length of 1.6 mm.

With the intention of effectively producing a product that preferably includes a surface tension modifying substance on its surface, it is also proposed in accordance with the pre-  
10 sent invention that such a substance is mixed with a granulated plastic material prior to injection moulding of the window, and to mould the window with said substance admixed with said granular plastic material.

15 Polyolefins, preferably an HD polyethylene have been preferred as the material used for injection moulding the window in accordance with the invention. A suitable surface tension modifying substance that has been found to function in admixture with the plastic granulate and for injection moulding in  
20 accordance with the inventive method are sorbitol esters and glycerol monooleates, for instance.

It will be understood that materials other than those mentioned in the foregoing can also be used, provided that  
25 these materials have similar properties than the mentioned materials and are able to provide corresponding end products.

## CLAIMS

1. A window for use in an adapter (3) for an IR gas analyser for the analysis of respiratory gases, where the gases flow through a through-penetrating passageway (9) in the adapter (3) with a window (8) disposed on mutually opposite sides of the passageway (9) so that an IR beam can be sent through the windows (8) and the passageway (9) containing said breathing gases, characterised in that the window (8) is a one-piece structure made of plastic material and having a round basic shape that includes a surrounding edge (8'') and a central part (8') which is sunken in relation to said edge (8'') and which constitutes the window through which the IR rays shall be able to pass.

15

2. A window according to Claim 1, characterised in that the plastic material is a polyolefin, preferably an HD polyethylene.

20 3. A window according to Claim 1 or 2, characterised in that the plastic material includes a surface tension modifying substance.

4. A window according to any one of the preceding Claims, characterised in that the window is formed by an injection moulding process.

5. A window according to any one of the preceding Claims, characterised in that the central part (8') of the window is arched in a direction away from the surrounding edge (8'').

6. A window according to any one of the preceding Claims, characterised in that the window has

been glued in a recess in a wall surrounding the through-penetrating passageway (9) in the adapter (3).

7. A window according to any one of Claims 1-5, characterised in that the window is fastened by ultrasound-welding or heat-welding in a recess in a wall surrounding the through-penetrating passageway (9) in the adapter (3).

8. A method of producing a window in accordance with any one of Claims 1-7, characterised by forming the window (8) by injection moulding a thermoplastic material in a mould in which injection of the plastic material into the mould is effected centrally in the centre of the ultimate or forthcoming window.

9. A method according to Claim 8, characterised by mixing a surface tension modifying substance in the thermoplastic material prior to the injection moulding process.

10. A method according to Claim 8 or 9, characterised by effecting the injection moulding process in a preheated mould tool.

1/6

Fig. 1a




Fig. 1b






Fig. 1c



2/6





3/6

Fig. 3a




Fig. 3b





Fig. 3c



4/6

Fig. 4a





Fig. 4b



5/6

Fig. 5a




Fig. 5b





Fig. 6



6/6

Fig. 7





Fig. 8



# INTERNATIONAL SEARCH REPORT

International application No.  
PCT/SE 2004/000617

## A. CLASSIFICATION OF SUBJECT MATTER

IPC7: A61B 5/08, G01N 21/03, G01N 33/497, B29C 45/18  
According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: A61B, B29C, G01N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-INTERNAL, WPI DATA, PAJ

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5693944 A (RICH), 2 December 1997 (02.12.1997), column 9, line 31 - column 10, line 18, figures 5, 6, cited in the application  --	1-7
A	US 6216692 B1 (TODOKORO ET AL), 17 April 2001 (17.04.2001), column 1, line 33 - line 61, figure 6, cited in the application  --	1-7
A	PATENT ABSTRACTS OF JAPAN vol.011, no. 114 10 April 1987 (1987-04-10) & JP 61258718 A (MATSUSHITA ELECTRIC IND CO LTD), 17 November 1986 (1986-11-17) abstract  -- -----	8-10

☐ Further documents are listed in the continuation of Box C.

☒ See patent family annex.

\* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier application or patent but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search  
3 August 2004

Date of mailing of the international search report  
04 -08- 2004

Name and mailing address of the ISA/  
Swedish Patent Office  
Box 5055, S-102 42 STOCKHOLM  
Facsimile No. +46 8 666 02 86

Authorized officer  
BO GUSTAVSSON/BS  
Telephone No. +46 8 782 25 00



# INTERNATIONAL SEARCH REPORT

Information on patent family members

03/07/2004

International application No.

PCT/SE 2004/000617

US	5693944	A	02/12/1997	CA	2198889 A,C	14/03/1996
				WO	9607886 A	14/03/1996
-----						
US	6216692	B1	17/04/2001	JP	2000074822 A	14/03/2000
				US	6512581 B	28/01/2003
-----						